

Product Description: Duracoat Road Marking Paint is formulated for use on concrete and bituminous surfaces forming roads, curbs and airfield runways. It is based on a rubberised resin coupled with good quality pigments and selected fillers. It is characterized by hard wearing film properties which give good durability on normal traffic pressure.

Finish: Matt

Application: By brush or road marking machine.

Thinning: No thinning is required. However if thick on storage restricted thinning may be applied using Duracoat Road Marking Thinner. Stir thoroughly on opening.

Colour Range: White, Black, Yellow and Red. May be available in other colours on request.

Drying time: Surface Dry: 5-10 minutes
Traffic free- 30 minutes at 25⁰ c

Cleaning: Clean all equipment with Duracoat Road Marking Thinner immediately after use.

Spread rate: At thickness of 3mm, the spreading rate is 6 – 8 square metres per litre depending on surface porosity.

Pack Size: 1 litre, 4 litre, 20 litre

SPECIFICATION

- Ensure surface is free of loose gravel and dusts.
- Never apply on wet surface. If after rain allow full drying before application.
- **Bitumen Surfaces:** One coat is normally sufficient on bitumen surfaces.
- **Paving Blocks, Concrete Plaster Surfaces:** Two coats are necessary if application is on paving blocks, allowing 30 mins. between coats. The first coat has to be thinned a little more for adhesion.