



Product Name: CRYSTALLINE
Crystal Effect Coating
Product Code: 110

DESCRIPTION

CRYSTALLINE is a water-based decorative finish for indoor use, consisting of waterborne styrene-acrylic emulsion enriched with metallic pigments and special fillers.

SPECIFICATION

- ✓ CRYSTALLINE features a unique crystalline effect that stands out most when near light sources.
- ✓ CRYSTALLINE is washable
- ✓ The product is non-hazardous if used according to its specifications.
- ✓ CRYSTALLINE can be applied to all kinds of plaster surfaces, as well as wood and metal panels, as long as they are treated with appropriate primers.

APPLICATION INSTRUCTIONS

Ensure that the surface is clean, dry and free from peeling paint or any substance that may compromise adhesion.

Prime the surface using the specific decorative primer Sandeco Uniprimer.

Using a varnish brush, apply first coat of Crystalline thinned with %25 of water and let them dry for minimum 3 hours before applying the finish.

Spread the product onto the surface with alternate brushstrokes, taking care to level the amount evenly.

Make sure that both the ambient temperature and the substrate temperature are between +5°C and +35°C



Product Name: CRYSTALLINE
Crystal Effect Coating
Product Code: 110

TECHNICAL FEATURES & PHYSICAL CONSTANTS

COLOURS	Available in a range of SANDECO special color card which can be further increased with special colors
DENSITY	1,25 ± 0,02 gr/cm ³
VISCOSITY	115- 125 KU
PH	8 - 9
VOLUME SOLIDS, %	52 ± 2
GLOSS GRADE	Matt
FLASH POINT	Non-flammable.
THINNING	Water
DRYING TIME	Dry-to-touch, 2 - 3 hours / In depth, 24 Hours (recorded at 23°C)
COVERAGE	Depending on porosity of surface and environmental conditions 0.130 - 0.140 L/m ² per coat
TEMPERATURE FOR APPLICATION	+ 5 °C - + 35 °C
APPLICATION TOOLS	Varnish Brush
SIZES & PACKAGING	1Lt - 2,5Lt
STORAGE AND SHELF LIFE	1 year, unopened in cool frost-free conditions
WARNING	Keep out of the reach of children. Avoid contact with skin and eyes