

Product Description: Basco Autoguard Cellulose Primer Surfacer is an automotive primer for Auto-finishes on motorcars, trucks, tractors, etc. It is based on a combination of Nitrocellulose and hard quality alkyd resins. Pigments include fillers and high quality inorganic materials that all combine to give a hard fast drying primer.

Finish: Matt

Application: By spraying only, at a pressure of 40-55 p.s.i.

Thinning: Basco Standard Thinner, best mixed at a volume ratio of 1:1 with Cellulose Primer Surfacer.

Dry Time: Touch Dry 5-10 mins in fair weather, overcoatable 30- 60 mins,

Cleaning: Clean equipment with Basco Standard Thinner immediately.

Colour Range: Grey, or as required.

Overcoats: Basco Autoguard Cellulose, Fast Dry or Two Pack Acrylic finishes.

Pack Sizes: ½ litre, 1 litre, 4litres.

SPECIFICATIONS

- Surface to be primed must be clean, dry, free from dust, oil, grease or any contaminant.
- Sanding down is best when abrasive paper is introduced onto water wet primed surface.
- Filling or smoothing primed surface can be done using Basco Spot Putty on dry Primer.
- Due to its fast air drying formulation the lid must be tightly replaced on unused primer in can.
- Keep away from naked flame. **INFLAMMABLE.**
- Avoid contact with skin or eyes by wearing goggles and protective clothing.
- Spray in well ventilated areas only.