



Duracoat Soft Satin Emulsion

Features

- Outstanding stain resistance
- Excellent mar and scuff resistance
- Provides mildew resistant coating
- Excellent flow and brushability
- No added lead
- Meets European Union VOC standard 2010.

General Description

Duracoat Soft Satin Emulsion is a premium quality waterbased paint formulated to give a soft satin finish to interior surfaces. It is extremely durable, fully washable and stain resistant paint suitable for high traffic areas. It is also ideal for living room, children's room, ceiling, columns, partitions, kitchen and bathrooms.


Recommended for

Living rooms, bed rooms, dining rooms, kitchens, bathrooms, commercial buildings where satin finish with highest performance characteristics are desired.

Limitations

Do not apply when the temperature is below 10°C.

Product Information

Colour Range : Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandek and Duracoat Colour Plus Fandek	Technical Data White
	Finish -Soft Satin
	Spread Rate -12-14 Sq. Mt./Ltr when applied on a smooth plaster
Special Colors : Special colors can be made available on request	Drying time - Surface dry -20-30 mins - Recoating time -3 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application -By Brush, Rollers, Conventional Spray
Technical Assistance: If in doubt please contact our Technical department on 82355/954	Thinning -Up to 25% (Vol.) water if applied by brush or roller. If applied by spray, more water may be needed to adjust to sprayable viscosity.
	Cleaning -Clean all equipments with water. Spray equipment should be given a final rinse with white spirit to prevent rusting
	Volatile Organic Compounds (VOC) - < 30 gms/ltr

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

New Unpainted Cement or Plaster surfaces:

Apply one coat of Duracoat Universal Undercoat or Duracoat Emulsion Undercoat followed by 2-3 coats of Duracoat Soft Satin Emulsion.

Previously painted surface :

Clean the surface and remove loose, flaking and powdery materials. Apply one coat of Duracoat Universal Undercoat or Duracoat Emulsion Undercoat followed by 2-3 coats of Duracoat Soft Satin Emulsion

For smooth uniform finish use Duracoat Smotex Lite/Ekogips Satin plaster for skimming.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Disposal information:

Dispose of in accordance with County regulations. Dry, empty containers may be given to scrap dealers for recycling.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

Post Application Instructions

The best thing to remove wall stains is to remove it immediately. For removing stains, sponge clean with mild soap/detergent solution and wipe clean. For better washability ensure the paint surface is cured for 1 week.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya
Tel:+254-20-6823555/954, Fax: +254-20-6823956 www.bascopaints.com