

## **Basco Undercoat**

---

**Product Description:** An Economy quality multi purpose undercoat which ensures good obliterating properties. Suitable for interior and exterior use on all types of surfaces.

**Finish:** Matt

**Application:** By Brush, roller, spray

**Thinning:** Where necessary thin with Duracoat White Spirit to ease brushing and for spray application

**Drying Time:** 4-6 hours, over coating best after overnight drying in normal conditions

**Cleaning:** Clean all equipment with Duracoat White Spirit

**Colour Range:** Available in white

**Spread Rate:** 11-13 sq. mts per litre when properly applied on smooth surfaces. Spreading rate will vary on rough surfaces.

**Pack Sizes:** 1 litre, 4 litres, 20 litres

### **SPECIFICATIONS:**

**Wood Surfaces:** Prepare surface by sanding to smooth, then apply one coat of Basco Wood Primer before applying one coat of Basco Undercoat. Allow overnight drying between coats. The Basco Undercoat must be overcoated with the desired finish.

**Metal Surfaces:** Prepare surface by degreasing, sanding with abrasive cloth and cleaning then apply one coat of Basco Matt Primer Red Oxide before applying one coat of Basco Undercoat. Allow overnight drying between coats. The Basco Undercoat must be overcoated with the desired finish.

**Previously Painted Surfaces:** Surfaces must be clean, dry and free from loose, flaking material. Surface must be cleaned and rubbed down with sand paper to a smooth surface. Apply one coat of Basco Undercoat, allow overnight drying before applying the desired finish.