



DuraCoat
ASK THE EXPERTS

Basco Permastic Wood Glue

Features

- Good Bond Strength.
- Water based
- Easy to apply

General Description

Basco Wood Glue is a water-based adhesive based on PVA and Homopolymer Emulsion for Bonding wood substrates.

Recommended for

For Wood , Flat Laminates, Plywood & MDF Boards

Application Condition

Do not apply when air and surface temperatures are below 10°C and above 35°C.

Product Information

	Technical Data	
Pack sizes : 1/4kg, 1/2kg & 1kg	Appearance	White Viscous Liquid
	Spread Rate	Depending on film thickness and nature of surface.
Technical Assistance: If in doubt please contact our Technical department on 6823555/954	Drying time @25 °C	
	- Surface dry	1-2 hours
	- Full Cure	6-8 hours
	- Full Strength	After 7 days
	Cleaning	Clean all equipment's with Water .
	pH-5-6	
	Application: By Brush Or Spatula	

Basco Permastic Wood Glue

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Moisture Content of surface should not exceed 12% prior to application.

Application Procedure.

Stir the container well before use, apply a homogeneous even coat on both the surface to be bonded, allow to dry for 2-3mins then press together with enough pressure using clamp for 6-8 hours. Wipe off excess material with a clean damp cloth before drying.

Health & Safety Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment's.

Precautions

- Stir thoroughly before and during use
- Always use good quality brush
- Always pre test on a small area first
- Sufficient pressure should be applied to have good bond strength before removing.

Note

- **Container should be closed tightly after use to avoid skin formation.**

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information