## DURACOAT FUNGICIDAL EMULSION - MATT

DDE 5

**Product Description:** This is a high quality emulsion paint designed specially for areas that have high algae, mould and fungal atmospheres, as often found in coastal regions. It is for application on internal or external of buildings. DuraCoat Fungicidal Emulsion Matt is suitable for new and previously painted surfaces on plaster, cement, brick, ceilings, walls, hardboards, softboards etc

Finish: Matt

Application: By Brush, roller, conventional spray

**Thinning:** It is recommended that clean water be used to thin to facilitate brushing, good flow and eliminating brush marks. The first coat which is usually regarded as a sealer should be thinned slightly more than subsequent coats.

**Drying time:** Touch Dry: 10-15 minutes Re-coating Time: 2-3 hours

**Cleaning:** Clean all equipment with water

**Colour Range**: Available in a wide range of colours from DuraCoat Colour Card and DuraCoat Classic Fan Deck.

**Spread Rate:** The spread rate varies considerably depending on the texture, porosity of the surface being painted. The approximate spread rates are as follows:

Types of surface	New or Unpainted	<b>Previously Painted</b>
Smooth plaster	14-16 sq. mts per litre	15-17 sq. mts. per litre
Wood float plaster	11-13 sq. mts per litre	12-14 sq. mts per litre
Rough cast	5-7 sq. mts per litre	6-8 sq. mts per litre

Pack Sizes: 1 litre, 4 litres, 20 litres

## **SPECIFICATIONS:**

Ensure surface to be painted is clean, dry, and free from dusts, grease, oil or any loose material.

a) New Cement or Plaster Surfaces: If the surface is dry and absorbent, the first coat should be thinned with up to 10 % of water. Follow up with one or two coats of unthinned paint. Where one coat is recommended, avoid thinning altogether.

- **b) Brick and Asbestos Surfaces:** These should be sealed with one coat DuraCoat Acrylic Sealer to reduce absorption followed by two coats of DuraCoat Fungicidal Emulsion Matt.
- c) **Previously Painted Surfaces:** If the existing paint work is in good condition, then the surface should be cleaned, sanded down before applying two coats of Duracoat Fungicidal Emulsion Matt.

## Please note:

- ▶ When over coating a dark shade with a light shade, three coats may be required.
- On dark shades like bright Reds, Greens, Oranges, an additional coat will be required as some shades have low opacity. Alternatively, a Duracoat Emulsion Undercoat of a similar colour could be applied before applying the final coats of paint finish.
- Due to technical constraints, certain dark colours tend to fade if exposed to UV light especially in tropical climates. For further details contact our Technical Service department