



Duracoat Aqua Wood Primer

Features

- Easy application
- Excellent covering
- Superior wood penetration and sealing properties
- Quick drying
- Easy to sand
- Excellent adhesion
- Low odor and Low VOC

General Description

A premium acrylic latex primer undercoat for use on new or previously painted woodworks. It provides optimum sealing, excellent adhesion, resistance to peeling and cracking with maximum hiding. This product contains a tannin blocker to resist wood stains thus sealing and protecting bare wood surfaces such as siding, trim, doors and windows


Recommended for

Wooden furniture, Doors, windows, trim

Limitations

Do not apply when the temperature is below 10°C.

Product Information

Colour Range : White	Technical Data White
	Finish Matt
	Spread Rate 9-12 Sq. Mt./Ltr The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface
Special Colors : NA	Drying time - Surface dry 20-30 mins - Recoating time 4 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application By Brush
Technical Assistance: If in doubt please contact our Technical department on 82355/954	Thinning Up to 10% (Vol.) with water. Dilution above this will affect final performance
	Cleaning Clean all equipments with water.
	Volatile Organic Compounds (VOC) < 50 gms/ltr

Duracoat Aqua Wood Primer

Surface Preparation

The wood must be clean and dry, and free of dust, oily residues or products that may limit adhesion.

New Wood:

- Sand the surface using 150/180-grain sandpaper.
- Mix the product thoroughly and apply it with a brush.
- After 4 hours, apply if necessary a second coat of product, without sanding, leave to dry for at least 4-6 hours, after which sand with 280/320-grain sandpaper, before applying finish coats.

Previously painted wood :

- Sand with 100/120-grain sandpaper until the complete removal of the pre-existing coating.
- Complete the sanding with 150/180-grain sandpaper.
- Remove the sawdust.
- Mix the product thoroughly and apply it with a brush.
- Proceed as stated for use on new wood.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information