



DuraCoat
ASK THE EXPERTS

Duracoat Superfast Emulsion

Features

- Non Toxic
- Excellent hiding power
- Outstanding durability
- Allows surface to breathe easily
- Excellent flow and leveling
- Better coverage

General Description

Duracoat Superfast Emulsion is a trade quality emulsion paint used for interior walls and ceilings. It has excellent hiding power and the porous nature of the film allows new surfaces to breathe and dry out easily. It contains lead free pigments making it non-toxic.


Recommended for

Interior walls and ceilings, warehouses, Low cost housing

Limitations

Do not apply when the temperature is below 10°C.

Product Information

Colour Range : Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandeck and Duracoat Colour Plus Fandeck	Technical Data	
	Finish	Matt
Special Colors : Special colors can be made available on request	Spread Rate	12-14 m ² /l when applied on a smooth, non porous surface
	Drying time - Surface dry - Recoating time	20-30 mins 3 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application	By Brush, Rollers, Conventional Spray
Technical Assistance: If in doubt please contact our Technical department on 6823555/954	Thinning	Up to 40% (Vol.) with water if applied by brush or roller. If applied by spray, more water may be needed to adjust to sprayable viscosity.
	Cleaning	Clean all equipments with water. Spray equipment should be given a final rinse with Duracoat White Spirit to prevent rusting
 DuraCoat ECO FRIENDLY PAINT ASK THE EXPERTS <small>This product is environmentally friendly and has low VOC (volatile organic compounds)</small>	Volatile Organic Compounds (VOC)	< 30 gm/l

Duracoat Superfast Emulsion

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

New Unpainted Cement or Plaster surfaces: Apply 2-3 coats of Duracoat Superfast Emulsion.

Unpainted Hardboards or Plaster Boards: Apply one coat of Duracoat White or Pink Wood Primer followed by 2-3 coats of Duracoat Superfast Emulsion.

Previously painted surface :

If the existing paint work is in good condition, the surface should be sanded, cleaned, dust free and 2-3 coats of Duracoat Superfast Emulsion applied.

For smooth uniform finish use Duracoat Smotex Lite/Ekogips Satin plaster for skimming.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Disposal information:

- Dispose of in accordance with County regulations. Dry, empty containers may be given to scrap dealers for recycling.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

Post Application Instructions

The best thing to remove wall stains is to remove it immediately.

For removing stains, sponge clean with mild soap/detergent solution and wipe clean.

For better washability ensure the paint surface is cured for 1 week.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information