

Tosha Emulsion

Product Description: Duracoat Tosha Emulsion is a trade grade emulsion paint used for interior walls. It is based on Acrylic copolymer emulsion with good quality pigments and extenders. It has excellent hiding power and the porous nature of the film allows new surfaces to breathe and dry out easily. It can also be used as an undercoat.

Finish	: Matt
Application	: By Brush, roller or spray
Thinning	: 30-40% by Volume
Drying time	: Touch dry: 15-20 min Re coating: 2 hours
Cleaning	: Clean all equipment with water.
Colour Range	: White, Soft white, Cream, Vanilla, Magnolia
Spread Rate	: 10-12 sq.mt/ltr. The spread rate varies considerably depending on the texture, porosity of the surface being painted.
Pack Sizes	: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

- I. New Unpainted Concrete surface:** All surfaces must be clean, dry and sanded. Apply three coats of Tosha Emulsion directly with the recommended dilution.
- II. Previously Painted Surfaces:** If existing paint work is in good condition, the surface should be cleaned, sanded and then apply three coats of Tosha Emulsion.
- III. Brick and Asbestos:** These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by three coats of Tosha Emulsion paint.
- IV. Unpainted Hardboards or Plaster Boards:** Apply one coat of Duracoat White or Pink Wood Primer followed by three coats of Tosha Emulsion Paint.