



**DuraCoat**  
ASK THE EXPERTS

# Duracoat Super gloss Enamel

## Features

- For exterior and interior use
- Outstanding adhesion
- Extremely durable high gloss finish
- Resistant to weather
- Excellent color retention
- Withstands repeated washing
- Excellent resistance to household stains

## General Description

Duracoat Super gloss Enamel is a premium quality protective finish having a rich deep gloss on properly prepared surfaces. This premium quality paint is based on high quality oil modified alkyd resin reinforced with polyurethane and high grade lightfast pigments.

## Recommended for

It is suitable for use on wood, metal and plaster.

## Limitations

Do not apply when the temperature is below 10°C.

## Product Information

<b>Colour Range :</b> Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandeck and Duracoat Colour Plus Fandeck	<b>Technical Data</b>	
	<b>Finish</b>	Full Gloss
	<b>Spread Rate</b>	12-15 m <sup>2</sup> /l on smooth, non porous surfaces
<b>Special Colors :</b> Special colors can be made available on request	<b>Drying time</b> - <b>Surface dry</b> - <b>Recoating time</b>	2-4 hours 16 hours
<b>Pack sizes :</b> 1ltr, 4 ltrs, 20 ltrs	<b>Application</b>	By brush, roller or spray
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 682355/954	<b>Thinning</b>	Supplied ready for use but may be thinned up to 10% with Duracoat White spirit for ease of brushing. Avoid over thinning. Stir well before use.
<b>DOES NOT CONTAIN LEAD</b>	<b>Cleaning</b>	Clean equipment with Duracoat White Spirit.

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material.

**New wood surfaces:** Surface must be clean and dry. Apply one coat of Duracoat Pink or White Wood Primer or Aluminium Wood Primer followed by one coat of Duracoat Universal Undercoat. When fully dry apply two coats of Duracoat Super gloss Enamel allowing 16 hours drying time between coats.

**Previously painted surfaces:** Rub and clean all loose flaking and powdery material from the existing surface. Rub down using sand paper to provide key. Apply two coats of Duracoat Super gloss Enamel allowing 16 hours drying time between coats.

**Metal Surfaces:** Apply one coat of Duracoat Matt Primer Red Oxide or Duracoat Zinc Phosphate Primer followed by one coat of Duracoat Universal Undercoat. Follow on with two coats of Duracoat Super gloss Enamel allowing 16 hours drying time between coats. Also see technical data on primers for specific metals.

**Plaster and Cement Surfaces:** The surface to be painted must be dry and make sure there is no moisture on the surface. Apply one coat of Duracoat Universal Undercoat before applying two coats of Duracoat Super gloss Enamel allowing 16 hours drying time between coats.

### Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or inject. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

### Post Application Instructions

For removing stains, sponge clean with mild soap solution and wipe clean. Ensure a drying of 1 week before cleaning.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information