

**Product Description:** Duracoat Matt Finish is designed for use on wood, school board, metal or concrete surfaces where a matt finish is required. It is based on oil modified synthetic resin and good quality pigments. It provides a good grip for chalk when used on school boards.

**Finish:** Matt

**Application:** By Brush, roller or spray

**Thinning:** Supplied ready for use but for ease of application thin with DuraCoat White Spirit.

**Drying time:** Surface dry: 3- 4 hours  
Re-coating: 16 hours

**Cleaning:** Clean all equipment with DuraCoat White Spirit

**Colour Range:** Black and Green or as ordered.

**Spread Rate:** The approximate spread rate is 12-14 sq mt per litre, depending on the surface texture and porosity.

**Pack Sizes:** 1 litre, 4 litres, 20 litres

### **SPECIFICATIONS:**

**New Unpainted Concrete surface:** All surfaces must be clean and dry. The first coat may be eased for brushing or rolling with up to 10 % of DuraCoat White Spirit. Follow up with one or two coats of unthinned paint. Where one coat is recommended avoid thinning altogether.

**Metal Surfaces:** Apply one coat of DuraCoat Matt Red Oxide Primer followed by two coats of DuraCoat Matt Finish

**New wood surfaces:** Apply one coat of DuraCoat White Wood Primer followed by two coats of DuraCoat Matt Finish

**Previously painted surfaces:** Remove all loose and flaking paint. Apply two coats of DuraCoat Matt Finish.