

**Product Description:** Duracoat Roof Paint is designed for use on iron roofing sheets as a finish coat and is manufactured using the finest light fast pigments. It gives a tough durable film which has excellent durability in open weather.

**Finish:** Semi- gloss

**Application:** By Brush or spray on corrugated surfaces. Can also be applied with roller on flat surfaces

**Thinning:** Supplied ready for use but for ease of application thin with Duracoat White Spirit.

**Drying time:** Surface dry: 3- 4 hours  
Re-coating: 16 hours

**Cleaning:** Clean all equipment with White Spirit.

**Colour Range:** Red, Green and Blue

**Spread Rate:** 14-16 sq mts per litre when applied on a smooth, non porous surface.

**Pack Sizes:** 1 litre, 4 litres, 20 litres

**SPECIFICATIONS:**

**New (un-weathered) Galvanised Surfaces/G C I Sheets:** Degrease and apply one coat of Duracoat Two Pack Etching Primer. After 30mins and within 8 hours apply one coat of Duracoat Zinc Phosphate Primer followed by two coats of Duracoat Roof Paint allowing 16 hours drying time between coats.

**Previously Painted Surfaces:** Remove all loose flaking paint apply two coats of Duracoat Roof Paint allowing 16 hours drying time between coats.