

Product Description: DuraCoat Floor Paint is designed for use on internal concrete or cement floors. It is a hard wearing oil based coating, suitable for domestic floors and light traffic shaded walkways.

Finish: Semi-gloss

Application: By Brush.

Thinning: Use DuraCoat White Spirit, to ease brushing.

Drying time: Surface Dry: 3-4 hours
Re-coating Time: 24 hours

Cleaning: Clean all equipment with DuraCoat White Spirit

Colour Range: Red oxide, green, grey, blue, or as ordered.

Spread Rate: 14-15 sq. mts. per litre when applied on smooth surface. Spread rate will vary if applied on rough surfaces

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

New Unpainted Concrete surface: Make sure the surface is free from dust, grease, oil and contains no water (moisture). Apply two coats of DuraCoat Floor Paint allowing 24 hours drying time between coats. Apply a thinner coat initially to ensure penetration into the floor.

Previously painted Surfaces: Clean the surface and remove loose, flaking and powdery materials. Apply two coats of DuraCoat Floor Paint allowing 24 hours drying time between coats.

Please Note:

- I) DuraCoat Floor Paint should not be applied over polished or waxed surfaces.
- II) All new floors should be painted three months or over after plastering as water retention in floors may take longer than on walls.