

Product Description: A premium quality multi purpose undercoat which ensures good weathering and obliterating properties. Suitable for interior and exterior use on all types of surfaces.

Finish: Matt

Application: By Brush, roller, spray

Thinning: Where necessary thin with DuraCoat White Spirit to ease brushing and for spray application

Drying Time: 4-6 hours, over coating best after overnight drying in normal conditions

Cleaning: Clean all equipment with DuraCoat White Spirit

Colour Range: Available in white and a range of light shades from DuraCoat colour card

Spread Rate: 13-15 sq. mts per litre when properly applied on smooth surfaces. Spreading rate will vary on rough surfaces.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

Wood Surfaces: Prepare surface by sanding to smooth, then apply one coat of DuraCoat Wood Primer or DuraCoat Aluminium Wood Primer as may be required before applying one coat of DuraCoat Universal Undercoat. Allow overnight drying between coats. The Universal Undercoat must be overcoated with the desired finish.

Metal Surfaces: Prepare surface by degreasing, sanding with abrasive cloth and cleaning then apply one coat of DuraCoat Red Oxide, DuraCoat Zinc Chromate or Duracoat Red Oxide Zinc Chromate primer before applying one coat of DuraCoat Universal Undercoat. Allow overnight drying between coats. The Universal Undercoat must be overcoated with the desired finish.

Previously Painted Surfaces: Surfaces must be clean, dry and free from loose, flaking material. Surface must be cleaned and rubbed down with sand paper to a smooth surface. Apply one coat of DuraCoat Universal Undercoat, allow overnight drying before applying the desired finish.