



**DuraCoat**  
ASK THE EXPERTS

# Duracoat 2 Pack Polyurethane Varnish

## Features

- Excellent Flow and Leveling
- Excellent Chemical Resistance
- Excellent Durability
- Mark Proof Film

## General Description

Duracoat 2 pack Polyurethane Clear Varnish is a premium quality varnish that can be applied on all types of timber surfaces. It is specially formulated to have hard mark proof film with good wear and chemical resistance.

## Recommended for

Interior & Exterior Use

## Application Condition

Do not apply when air and surface temperatures are below 10°C and above 35°C.

## Product Information

<b>Product Range :</b> Available in Gloss , Satin & Matt	<b>Technical Data</b>	
	<b>Finish</b>	Clear Gloss , Satin & Matt
	<b>Spread Rate</b>	15-16m <sup>2</sup> /l depending on film thickness and nature of surface.
<b>Pack sizes :</b> 1ltr, 4 ltrs	<b>Drying time @25 °C</b>	
	- <b>Touch dry</b> - <b>Recoating time</b>	2 hours 14 hours Achieves Full Hardness after 7 days of Application
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	<b>Application</b>	By Brush or Spray
	<b>Cleaning</b>	Clean all equipment's with Duracoat 2 Pack Poly Thinner.
<b>Pot Life-</b> 4-6 Hours @25°C	<b>Mixing Ratio</b>	3PartsClear:1Part Hardener : 1Part 2 Pack Poly Thinner

## Duracoat 2 Pack Polyurethane Varnish

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. All traces of Wax or Oil should be removed by power sanding particularly if wax had been used on the surface before. Moisture Content of surface should not exceed 12% prior to coating.

#### New Wooden Surface:

Apply 2 or 3 coats of Duracoat 2 Pack Polyurethane Varnish. Light Sanding In between coats will give homogeneous smooth Finish. 1<sup>ST</sup> coat can be diluted more which acts as a sealer coat .

#### Previously painted surface :

Remove all the previously coated surface by scrapping or sanding. Then apply Duracoat 2 Pack Polyurethane Varnish. as per the procedure for new wood surface.

### Health & Safety Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment's.
- Fire Hazard: Flammable

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Note

- **Container should be closed tightly after use to avoid skin formation.**

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya  
Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)