



Duracoat Tex silk

Features

- Excellent adhesion
- Excellent UV and weather resistant
- Does not retain dirt, cleans easily
- Will not crack with normal surface movement
- Exceptionally tough
- Water resistant
- UV resistant pigments, colours remain true for a long time
- Alkali and mold resistant
- Virtually odour free, user and environmental friendly

General Description

Duracoat Tex Silk is extremely durable, flexible exterior paint. Duracoat Tex Silk produces a high build stipple coating that is fully washable.. The pure acrylic resin confers exceptional weather resistance resulting in a long life protection of external building surfaces. Due to its high build stipple finish it also hides surface imperfections. Its unique formulation protects concrete from carbonation (Acts as anticarbonation coating).


Recommended for

Exterior Surfaces, high traffic areas like hallways, corridors, reception area, etc

Limitations

Do not apply when air and surface temperatures are below 10°C and above 35°C.

Product Information

Colour Range : Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandek and Duracoat Color Plus Fandek	Technical Data	
	Finish	Soft sheen
Special Colors : Special colors can be made available on request	Spread Rate	1-1.5 sq. mt/ltr depending on the application method and substrate
	Drying time - Surface dry - Recoating time	1-2 hours 12 hours
Pack sizes : 1ltr, 4 ltrs, 20 ltrs	Application	Roller
Technical Assistance: If in doubt, please contact our Technical department on 6823555/954	Thinning	No thinning required. DO NOT THIN
	Cleaning	Clean all equipments with water.
	Volatile Organic Compounds (VOC)	< 30 gm/l

Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Insufficient surface preparation will result in complete failure of the paint system in a short while

New Unpainted Cement or Plaster surfaces:

Apply one coat of Duracoat Tex silk Primer. Leave to dry for 4 hours. Apply one coat of Duracoat Tex Silk.

Previously Painted Surfaces in Sound Conditions:

Ensure surface is clean, dry and free from any contamination. When recoating on gloss paint, the surface must be abraded with sand paper. Apply one coat of Duracoat Tex silk Primer. After drying, apply one coat of Duracoat Tex Silk.

Previously Painted Surfaces in Unsound Conditions:

Loose, flaking, powdery material must be removed prior to painting. Walls which were previously painted with low grade paint, dampers, white wash, cement paints and lime wash must be completely sanded down to film base or original plaster. Any surface cracks or holes should be raked out and filled with Duracoat Permafill Flexible Crack filler. Treat surface for mould or algae if present with Duracoat Fungicidal Wash and ensure that the surface is completely dry. Apply one coat of Duracoat Tex silk Primer prior to applying Duracoat Tex Silk.

Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade two coats may be required
- For dark shades like bright Reds, Oranges, Yellow an additional coat may be required

Post Application Instructions

For removing stains, sponge clean with mild soap solution and wipe clean. Ensure a drying of 1 week before cleaning.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information