

Features

- Special iridescent effect
- Silky Appearance
- Perfect for creating classic and modern atmospheres.
- Easy to apply.
- Customized designs

General Description

Ultima Play Opal Fire is a super-premium decorative finish for interiors with special iridescent effect, soft to the touch and with a silky appearance. It is perfect for creating classic and modern atmospheres and easy to apply.

The product enables the realization of various decorative effects according to fancy and the application technique used, with degrees of iridescence depending on the amount of light reflected.


Recommended for

New and old interior plasters, interior concrete walls, Interior painted walls, interior gypsum walls

Limitations

Do not apply when the temperature is below 10°C. and above 40°C

Product Information

Colour Range : Available in wide range of colours from: *Ultima Play Opal Fire Shade Card	Technical Data	
	Finish	Silky Finish
Special Colours Special colours can be made available on request	Spread Rate	4-6 Sq. Mt./Ltr with 2 Coats when applied on a smooth surface.
	Drying time - Surface dry - Recoating time	1 Hours 6 Hours
Pack sizes : 1ltr, 4 ltrs	Application	By Brush, Plastic Trowel, Stainless Steel Trowel
Technical Assistance: For Further Guidance or Queries, call our helpline number on 0800221331 or reach us at 0206823555 / 0722 204 300 / 0733 333 940	Thinning	Do Not Thin. Ready to Apply
	Cleaning	-Clean all equipments with water immediately after use
	Volatile Organic Compounds (VOC)	< 50 gm/l

Surface Preparation

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material. Cracks and defects must be filled with the appropriate crack filler followed by the appropriate primer.

New Unpainted surfaces:

Apply one coat of Duracoat Vinyl Matt Deluxe or Duracoat Emulsion undercoat as a primer coat

Apply first coat of Ultima Play Opal Fire over the dry primer with the plastic or steel trowel, spreading the paint evenly.

Once the first coat has dried apply a second coat of Ultima Play Opal Fire with the plastic or steel trowel, using the tool in a rotating movement in crisscrossed movement to create a two-tone faceted effect.

Previously painted surface:

Clean the surface and remove loose, flaking and powdery materials.

Follow the procedure as for new unpainted surfaces.

Precautions

- Ensure good ventilation during application and drying.
- Store the product in ambient conditions in well ventilated locations and away from the source of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medication attention if symptoms persist in both cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

KEEP OUT OF REACH OF CHILDREN

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information