



Features

- Marble Effect
- Vivid & Bright Colours
- Highly Washable

General Description

Duracoat Ultima Play Stucco is a super-premium acrylic emulsion based glossy interior decorative coating which contains special additives and pigments in paste consistency applied with a trowel or spatula to get a marble finish.


Recommended for

New and old interior plasters, interior concrete walls, Interior painted walls, interior gypsum walls

Limitations

Do not apply when the temperature is below 10°C. and above 40°C

Product Information

Colour Range : Available in a Wide Range of Colors from Ultima Play Stucco Shade Card.	Technical Data	
	Finish	Gloss Finish
	Spread Rate	2-4 Sq. Mt./Kg
Special Colours Special colours can be made available on request	Drying time	
	- Surface dry	20 – 30 Min
	- Recoating time	8 - 10 Hours
Pack sizes :1Kg, 5Kg	Application By Steel Trowel, Spatula	
Technical Assistance: For Further Guidance or Queries, call our helpline number on 0800221331 or reach us at 0206823555 / 0722 204 300 / 0733 333 940	Thinning Do Not Thin. Ready to Apply	
	Cleaning -Clean all equipments with water immediately after use	
 Dura Coat ECO FRIENDLY PAINT ASK THE EXPERTS This product is environmentally friendly and has low VOC (volatile organic compounds)	Volatile Organic Compounds (VOC) < 50 gm/l	

Surface Preparation

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material. Cracks and defects must be filled with the appropriate crack filler followed by the appropriate primer.

New Unpainted surfaces:

Apply one coat of Duracoat Vinyl Matt Deluxe or Duracoat Emulsion undercoat as a primer coat.

Apply one or more even coats of Duracoat Ultima Play Stucco on the dry primer using the Steel Trowel to obtain a smooth and even surface.

Allow 8 to 10 Hours drying time between coats. The Final coat can be polished with a steel trowel by moving back and forth in an oscillatory motion pressing on the surface.

Previously painted surface:

Clean the surface and remove loose, flaking and powdery materials.

Follow the procedure as for new unpainted surfaces.

Precautions

- Ensure good ventilation during application and drying.
- Store the product in ambient conditions in well-ventilated locations and away from the source of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medication attention if symptoms persist in both cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc. before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality tool
- Always pre-test on a small area first

KEEP OUT OF REACH OF CHILDREN

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information