

Durabond 201

High Performance, flexible cementitious tile adhesive

Product Description : Durabond 201 is a high performance flexible cementitious, Polymer modified tile adhesive. It contains highest grades of cement, fillers, polymers and chemical additives to give it unique properties.

Uses : Durabond 201 is suitable for fixing :

- Vertical and Horizontal tiles
- Ceramic and Mosaic Tiles
- Porcelain Tiles
- Granite Tiles

Advantages :

- Highly flexible
- Easy to use with excellent workability
- Excellent adhesion to most substrates (cements screeds, concrete or lime mortars, etc.)
- High bond strength
- Water and weather resistant
- Suitable for indoor and outdoor application
- Non Toxic

Specifications:

Nature : Cementitious Powder
Color : Gray
Density : ~ 1.9 Kg/ltr
Open Time : Approximately 30 mins at 25°C
Pot life : Approximately 60 mins at 25°C
Mixing ratio : Approximately 5-6 ltrs for 25 kgs bag
Coverage : Approximately 3-4 kg/m²
Temperature : Min 5°C, Max 40°C (substrate)
Packaging : 25 Kg bag

Substrate preparation :

The substrate must be cured, mechanically strong, free from loose particles, grease, oils, paint, wax and sufficiently dry. All surfaces must as flat as possible.

Mixing :

Add 5-6 ltrs of clean water to suitable mixing container. Slowly add Durabond 201 powder to water and mix until a homogenous lump free paste is achieved. Do not add extra water or other ingredients after mixing.

Application : Apply Durabond 201 at 2-3 mm thickness directly to the concrete substrate using a notched trowel and spread the mortar evenly over the area to be tiled.