

DURACOAT SANDTEX TEXTURED FINISH

Product Description: Duracoat Sandtex Textured Finish is a high build textured coating that contains mould resistant fungicides. It is suitable for both interior and exterior decoration in domestic and commercial properties.

Finish: Matt, high build textured finish

Application: First apply with a large paint brush, an area of about 1sq meter. Then lay the surface off with light horizontal brush strokes before texturing with special texture rollers. Using different techniques, a variety of effects can be achieved.

Thinning: Supplied ready for use. No thinning at all recommended

Drying Time: Surface dry 2 – 4 hours.
Hard dry after 24hours

Cleaning: Clean all equipment with water immediately.

Colour range: Available in White, and very limited medium shades from Duracoat Colour Card, Duracoat Classic Fan Deck and Color Plus fandeck.

Spread Rate: 1 kg covers approximately 1sq. mtr. depending on surface porosity.

Pack Sizes: 1kg, 5kg, 25kg

SPECIFICATION

New Surfaces: Must be scrapped with sand paper and brushed off to remove any deposits and loose particles. For application on wooden surfaces apply one coat of Duracoat Universal Undercoat first.

Previously Painted Surfaces: All loose, flaking and unsound paint should be removed by sanding with the aid of wire brush. If surfaces are mould infected then sterilize with Duracoat Fungicidal Wash. Allow 24 hours drying time before applying Duracoat Sandtex Textured Finish.