

Duracoat Royale 100% Pure Acrylic Outdoor Protector

Product Description :

Duracoat Royale 100% Pure Acrylic Outdoor Protector is manufactured using 100% pure acrylic resin. The pure acrylic resin confers exceptional weather resistance resulting in a long life protection of external building surfaces. It is further enhanced with two potent algacides and preservatives for dry film protection which will resist mould and algae growth. Duracoat 100% Pure Acrylic Outdoor Protector is recommended for exterior use in highly humid and coastal weather conditions where the paint is subjected to severe weather.

Features/Benefits :

- 10 years guarantee
- Premium exterior durability
- Will not soften when flooded with water
- Attractive luxurious appearance
- UV resistant providing long term protection from the ageing effects of sunlight
- Does not retain dirt, cleans easily
- Will not crack with normal surface movement
- Virtually odour free, user and environment friendly
- Excellent adhesion
- Alkali and mould resistant
- Fully washable
- Exceptionally tough
- Water resistant
- Vast color range – over 4000 shades to chose from

Application methods :

For detailed information please refer to the instructions on the container.

- Can be applied by brush, roller or airless spray
- Stir well before use

Thinning :

Up to 25% (By volume) with water. **DO NOT** overthin as this will impair the final properties of the paint film.

Spreading rate :

Spreading rate varies according to the surface porosity and texture. Approximate spreading rates on different surfaces are given below.

Surfaces	Aprox. Spreading rate in Sq.Mt/Lt
Newly Plastered wall	12 – 14
Previously painted wall in good condition	13 – 17
Wood float / Cement rendered - new	10 – 12
Wood float / Cement rendered – previously painted	12 – 14
Concrete blocks - new	5 – 7

Concrete blocks - previously painted	6 – 8
Tyrolene and textured – new	2 – 4
Tyrolene and textured – previously painted	3 – 5

Shade range :

Available from BS 4800, Duracoat Classic and Color Plus fandeck. Special shades can be made available on request.

Pack Sizes :

Available in 1 Ltr, 4 Ltrs, and 20 Ltrs.

Good working practices :

- Read instructions carefully before painting
- Ensure good ventilation during paint application
- When using spray gun as an application tool, wear suitable clothing and protective equipments
- Wash hands with water and soap
- Keep unused paint cans tightly closed and away from children and pets

Hints and tips (for best results)

- Always read instructions
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Wise precautions :

- Ensure good ventilation during application and drying
- Avoid contacts with skin and eyes
- After contact with skin wash immediately with plenty of soap and water. In case of contact with eye, rinse immediately with plenty of water and seek medical advise.
- Keep out of reach of children