



DuraCoat
ASK THE EXPERTS

ULTIMA PLAY KRYSTAL

Features

- Wide Range of Customizable Decorations
- Transparent finish with micro crystals
- Multi Colour Effect

General Description

Ultima Play Krystal is a super-premium product with a finish able to create a wide range of customizable decorations. Can be realized transparency effects characterized by the presence of micro crystals with delicate shade multi color. The aesthetic variety achievable depend on the creative flair and juxtaposition of textures and colors.


Recommended for

New and old interior plasters, interior concrete walls, Interior painted walls, interior gypsum walls

Limitations

Do not apply when the temperature is below 10°C. and above 40°C

Product Information

Colour Range : Neutral	Technical Data	
	Finish	Gloss Finish
	Spread Rate	15-20 Sq. Mt./Ltr
Special Colours Special colours can be made available on request	Drying time - Surface dry 30 Min - Recoating time 2 Hours	
Pack sizes : 1ltr, 4 ltrs	Application	By Brush, Sponge
Technical Assistance: For Further Guidance or Queries, call our helpline number on 0800221331 or reach us at 0206823555 / 0722 204 300 / 0733 333 940	Thinning	Dilute with maximum 10% Water
 DuraCoat ECO FRIENDLY PAINT ASK THE EXPERTS <small>This product is environmentally friendly and has low VOC (volatile organic compounds)</small>	Cleaning	-Clean all equipments with water immediately after use
	Volatile Organic Compounds (VOC)	< 50 gm/l

Surface Preparation

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material. Cracks and defects must be filled with the appropriate crack filler followed by the appropriate primer.

New Unpainted surfaces:

Apply one coat of Duracoat Emulsion Undercoat followed by 2 Coats of Duracoat Vinyl Matt Deluxe.

Apply first coat of Ultima Play Krystal over the dry primer with the sponge or brush, spreading the paint evenly.

Previously painted surface:

Clean the surface and remove loose, flaking and powdery materials.

Follow the procedure as for new unpainted surfaces.

Precautions

- Ensure good ventilation during application and drying.
- Store the product in ambient conditions in well ventilated locations and away from the source of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medication attention if symptoms persist in both cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

Note

- When over coating a dark shade with a light shade three coats may be required
- On dark shades like bright Reds, Greens, Oranges an additional coat will be required as some shades have low opacity

KEEP OUT OF REACH OF CHILDREN

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya
Tel:+254-20-6823555/954, Fax: +254-20-6823956 www.bascopaints.com