

ULTIMA PLAY GLITZ

Features

- Festive Ambiance
- Metallic Finish
- Changes the mood with changing light

General Description

Ultima Play Glitz is a super-premium quality water based metallic emulsion which gives an elegant glittering effect which adds a new dimension of sophistication to your wall.

Different lighting arrangements change the hue and colour of the applied paint.

Recommended for

New and old interior plasters, interior concrete walls, Interior painted walls, interior gypsum walls

Limitations

Do not apply when the temperature is below $10^{\rm O}{\rm C}$ and above $40^{\rm O}{\rm C}$

Product Information

Colour Range:	Technical Data	
Silver, Gold, Bronze and many more shades from the Ultima Play Glitz Shade	Finish	Metallic Finish
Card	Spread Rate	7-9 Sq. Mt./Litre
Special Colours	Drying time	
Special colours can be made available on	- Surface dry	20 - 30 Min
request	- Recoating time	4 Hours
	Application	By Roller
Pack sizes:1ltr, 4 ltrs		For corners & edges, apply using sponge.
Technical Assistance: For Further Guidance or Queries, call our helpline number on 0800221331 or reach us at 0206823555 / 0722 204 300 / 0733 333 940	Thinning	Ready to use. Do Not Thin
	Cleaning	-Clean all equipments with water immediately after use
Dura Coat ASK THE EXPERTS This product is environmentally friendly and has low VOC (volatile organic compounds)	Volatile Organic Compounds (VOC)	< 50 gm/l

Surface Preparation

All surfaces to be painted must be clean, dry, and free from dust, grease, or any loose material. Cracks and defects must be filled with the appropriate crack filler followed by the appropriate primer.

New Unpainted surfaces:

- a) Wall
 - Apply one coat of Duracoat Vinyl Matt Deluxe or Duracoat Emulsion Undercoat as a primer.
 - Apply two or three coats of Duracoat Ultima Play Glitz over the dry primer with Roller
- b) Metal
 - Apply one coat of Duracoat Rustguard Metal Primer
 - Apply two or three coats of Duracoat Ultima Play Glitz over the dry primer

c) Wood

- Apply one coat of Duracoat Aqua Wood Primer
- Apply two or three coats of Duracoat Ultima Play Glitz over the dry primer

Previously painted surface:

- Clean the surface and remove loose, flaking and powdery materials.
- Follow the procedure as for new unpainted surfaces.

Precautions

- Ensure good ventilation during application and drying.
- Store the product in ambient conditions in well ventilated locations and away from the source of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medication attention if symptoms persist in both cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

KEEP OUT OF REACH OF CHILDREN

Refer to MSDS for additional health and safety information

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information