

Product Description: A semi matt oil based finish for use on walls, wooden surfaces and high traffic areas. It is made from high quality oil modified alkyd resins and selected light fast pigments.

Finish: Semi- matt (like the shell of an egg)

Application: By Brush, roller or spray

Thinning: Thin with DuraCoat White Spirit. Stir well on opening.

Drying time: Dust free 2-4 hours
Re-coatable 16 hours

Cleaning: Clean equipment with DuraCoat White Spirit

Colour Range: Available in a wide range of colours from DuraCoat Colour Card, DuraCoat Classic and Color Plus Fan Deck.

Spread Rate: 12-15 sq. m/lt depending on surface texture and porosity.

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

New wood surfaces: Surface must be clean, dry. Apply one coat of DuraCoat White or Aluminium Wood Primer followed by one coat of DuraCoat Universal Undercoat. Follow on with two coats of DuraCoat Eggshell Finish allowing 16 hours drying time between coats.

Metal Surfaces: Apply one coat of DuraCoat Red Oxide Zinc Chromate Primer to ferrous substrate and DuraCoat Zinc Chromate Primer to non-ferrous surfaces followed by one coat of DuraCoat Universal Undercoat. Follow on with two coats of DuraCoat Eggshell Finish allowing 16 hours drying time between coats

Plaster and Cement Surfaces: The surface to be painted must be dry and make sure there is no moisture on the surface. Apply one coat of DuraCoat Emulsion Undercoat before applying two coats of DuraCoat Eggshell Finish allowing 16 hours drying time between coat.