



# THE ULTIMATE EXTERIOR PAINT

## Product Description

Duracoat Silicone Exterior Emulsion is a High-Performance Premium Grade Exterior Paint Formulated with Unique Organo-Silicone Chemistry which Imparts Visible Water Repellency. It allows substrates to breathe almost unhindered. This Property Minimizes Potential for Peeling and Flaking from Entrapped Moisture. It is an External Finish.

## Features



Breathable

15 Years Warranty



Strong Water Repellency

Self-Cleaning Effect and Excellent Resistance to Microbial Attack



Has fungicide and dry film preservatives that make it Potent to Mould and Algae

## Recommended for

Exterior Residential & Commercial Applications where a Beautiful Low Sheen and Smooth Finish are Desired. It's Outstanding Durability Makes it Ideal for Severe Tropical Weather Conditions.

Available in a Wide Range of Colors from The Duracoat Classic and Duracoat Classic Fan-Deck from Duracoat Colour Mania Centre near you.

## Colour range



12,000+ COLOURS

## Finish



## Packs



1Ltr



4Ltrs



20Ltrs

## Application



ROLLER



BRUSH



SPRAY



# PROTECT YOUR WALLS FOR UP TO 15 YEARS

## Surface Preparation

### New Surface

Ensure the surface to be painted is dry especially in cases where plastering has just been carried out. It is recommended to allow 28 days as the curing time for new plaster.

Apply 3 coats of Duracoat Silicone Exterior Emulsion paint allowing 4 hours drying time between coats.

Use first coat diluted at 40% with water as a primer followed by 2 coats diluted at 20% with water. Do not over thin. If the wall is highly alkaline (pH above 9.5) then apply first coat of Duracoat Alkali Resistant Primer followed by 3 coats of Duracoat Silicone Exterior Emulsion.

### Previously Painted Surface

Strip all the old paint and remove all the loose particles before starting the above process.

In case of dents and holes use Duracoat Internal & External Skim Coat.

## Technical Data

| Coverage                     | Newly Painted Surfaces |
|------------------------------|------------------------|
| Cement Wood Float Plaster    | 8 - 10 Sq. Mt/Ltr      |
| Smooth Plaster               | 10 - 12 Sq. Mt/Ltr     |
| Concrete Blocks              | 5 - 7 Sq. Mt/Ltr       |
| Rough or Textured Paint      | 3 - 4 Sq. Mt/Ltr       |
| Reinforced Concrete Surfaces | 7 - 9 Sq. Mt/Ltr       |

## Precaution

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical attention.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

### PROTECTS AGAINST ALL WEATHER ELEMENTS



BascoPaintsKenya @basco\_paints @bascopaints



\* T&C Apply

