



**DuraCoat**  
ASK THE EXPERTS

# Duracoat Emulsion Undercoat

## Features

- Excellent whiteness & opacity
- Easy application
- Excellent coverage
- Good sealing properties
- Provides excellent adhesion to top coat emulsions
- Improves appearance of top coat

## General Description

A premium quality smooth flowing primer that provides excellent adhesion and sealing characteristics for interior & exterior surfaces.


## Recommended for

Ideally suitable for soft boards, gypsum, hardboard and cement plaster.

## Limitations

Do not apply when the temperature is below 10°C.

## Product Information

<b>Colour Range :</b> White and light colors	<b>Technical Data</b>	
	<b>Finish</b>	Matt
	<b>Spread Rate</b>	11-14 m <sup>2</sup> /l when applied on a smooth, non porous surface
<b>Special Colors :</b> Special colors can be made available on request	<b>Drying time</b> - <b>Surface dry</b>	20-30 mins
<b>Pack sizes :</b> 1ltr, 4 ltrs, 20 ltrs	<b>- Recoating time</b>	3 hours
	<b>Application</b>	By Brush, Rollers, Conventional Spray
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	<b>Thinning</b>	Up to 20% (Vol.) with water if applied by brush or roller. If applied by spray, more water may be needed to adjust to sprayable viscosity.
 <p><b>DuraCoat   ECO FRIENDLY PAINT</b> ASK THE EXPERTS This product is environmentally friendly and has low VOC (volatile organic compounds)</p>	<b>Cleaning</b>	Clean all equipments with water. Spray equipment should be given a final rinse with Duracoat White Spirit to prevent rusting
	<b>Volatile Organic Compounds (VOC)</b>	< 30 gm/l

## Duracoat Emulsion Undercoat

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

**New surfaces:** Apply one coat of DuraCoat Emulsion Undercoat followed by two coats of desired Duracoat Emulsion top coat allowing 4 hrs of drying after the Undercoat.

**Metal Surfaces :** Not recommended.

**Previously painted surfaces:** Remove all old flaking paint from the surface and rub down the surface. Apply one coat of Duracoat Emulsion Undercoat followed by two coats of desired Duracoat Emulsion top coat, allowing 4 hrs of drying after the Undercoat.

**For smooth uniform finish use Duracoat Smotex Lite/Ekogips Satin plaster for skimming.**

### Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Post Application Instructions

Apply any Duracoat range of emulsion paint over Duracoat Emulsion Undercoat

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disposal information:

Dispose of in accordance with County regulations. Dry, empty containers may be given to scrap dealers for recycling.

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya  
Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)