



**DuraCoat**  
ASK THE EXPERTS

## Duracoat Real Roc Textured Paint

### Features

- .Hides and Protects Surface Imperfections and Hairline Cracks.
- .Flexible, Tough and Weather resistant Textured Coating.
- .Excellent Antifungal, Anti Algal and Anti Mould Properties
- .Excellent Adhesion and Durability.
- .Crack Resistant
- .Good Alkali Resistant Properties.
- . Flexible film which moves with temperature and bridges hairline cracks

### General Description

Duracoat Real Roc textured paint is formulated by using special type of acrylic resin. It contains inert pigments, fillers, tough aggregates and unique additives to resist fungus, algae and mould growth. It protects the exterior surfaces from extreme conditions.


### Recommended for

Interior and exterior applications. It can be applied on a variety of surfaces such as plaster, brickwork, concrete etc. by using suitable priming coat.

### Limitations

Do not apply when the temperature is below 10°C and above 40 °C.

### Product Information

<b>Colour Range :</b> Available in a wide range of colors from Duracoat Color Chart, Duracoat Classic Fandeck and Duracoat Colour Plus Fandeck	<b>Technical Data</b>	
	Finish	- Textured/Matt Finish - 0.5,1mm,2mm &3mm
<b>Special Colors :</b> Special colors can be made available on request	Spread Rate	- Stone Finish : 3-4 kg /Sqm -0.5mm finish: 2.75- 3 kg/Sqm -1mm finish: 2.75- 3 kg/Sqm -2mm finish: 2.75- 3 kg/Sqm -3mm finish: 4.5- 4.75 kg/Sqm  Actual Coverage capacity may vary depending on Application Method and Surface Condition.
	Drying time @25 °C	- Surface dry -2 Hour - Hard Dry -12 hours
<b>Pack sizes :</b> 5 Kgs & 30Kgs	Application	-By Stainless Steel Trowel & Finishing with Plastic Trowel for creating the texture
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 82355/954	Thinning	-DO NOT THIN. Product is ready for use.
	Cleaning	-Clean all equipments with water.
	VOC	<30gm/kg

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. Cracks and defects should be filled with appropriate crack filler followed by appropriate primer.

**New unpainted concrete Surface:** Apply one coat of Emulsion Undercoat. Followed by 1 coat of Real Roc Textured Paint.

**Brick and Asbestos:** These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by one coat of Emulsion Undercoat. Followed by 1 coat of Real Roc Textured Paint.

**Previously Painted Surfaces:** If existing paint work is in good condition, the surface should only be cleaned, sanded and one coat of Undercoat be applied. Followed by 1 coat of Real Roc Textured Paint.

### Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould, etc before application of the paint system.

### Application

- Stir thoroughly before and during use
- Always use good quality Tools.
- Always pre test on a small area first
- Always use same the batch number from corner to corner to avoid variations.
- While using Multiple Batches it is recommended to mix it together to avoid Variations.

### Note

.We strongly recommend that ordinary painters are not employed to carry out the application of Real Roc textured finishes as certain specialty skills have to be passed on so as to get the desired finish and life from these products.

.For more protection it can be Over coated with Premium Quality Dura coat Exterior Emulsion Paints after Drying.

**KEEP OUT OF REACH OF CHILDREN**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya

Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)