

Product Description: DuraCoat Penetrating Primer is based on high quality resins, pigments and extenders. It is designed to bind loosely bound powdery and flaking surfaces. It can also be used on new and very porous plaster surfaces where prior binding is required before painting. It is recommended for use when redecorating external walls which have been neglected, and water seepage has led to deterioration of paint coats.

Finish: Matt

Application: By Brush or Roller. Apply liberally for best results.

Thinning: Supplied ready for use, but restricted thinning may be applied for use on rough textured surfaces using DuraCoat White Spirit. Stir thoroughly before applying.

Drying time: Touch Dry: 3-4 hours.
Hard Dry: 24 hours

Cleaning: Clean all equipment with DuraCoat White Spirit

Colour Range: Clear with an off white marker pigment

Spread Rate: 14-16 sq. mts. per litre when properly applied on smooth surfaces. Spreading rate will vary on rough surfaces

Pack Sizes: 1 litre, 4 litres, 20 litres

SPECIFICATIONS:

Surfaces to be treated must be free from loose, flaking materials which must be removed by scrapping.

Precaution

- I. Wear gloves and goggles during application as this can be irritating to the eyes and skin. Use this product in well ventilated areas
- II. In the event of contact with skin, wash the affected areas with water and soap immediately. In the event of contact with eyes, rinse with clean water and seek medical attention immediately.
- III. The material is flammable. Keep away from naked flames, and smoking close to the material should not be permitted.