



**DuraCoat**  
ASK THE EXPERTS

## Duracoat Single Pack Polywood Seal Varnish

### Features

- Excellent Gloss Retention.
- Preserves and Enhances Wood Grain
- Tough and Durable Finish
- Resists Household Stains

### General Description

Duracoat Polywoodseal is a single pack polyurethane varnish primarily intended for all type of interior wood work. It offers natural look to the wood and protects it from water, dilute domestic acids, alcohol and oil. It is also suitable for Wood flooring work, chipboard, hardboard, woodwork furniture, and all other interior timber surfaces.

### Recommended for

Interior Use only

### Application Condition

Do not apply when air and surface temperatures are below 10°C and above 35°C.

### Product Information

<b>Product Range :</b> Available in Gloss & Matt Finish	<b>Technical Data</b>	
	<b>Finish</b>	Clear Gloss or Matt
	<b>Spread Rate</b>	16-18 m <sup>2</sup> /l depending on film thickness and nature of surface.
<b>Pack sizes :</b> 1ltr, 4 ltrs	<b>Drying time @30 °C</b>	
	- <b>Surface dry</b>	4 hours
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	<b>Application</b>	By Brush, Spray or Cloth Pad
	<b>Cleaning</b>	Clean all equipment's with Duracoat White Spirit .
	<b>Thinning</b>	Supplied Ready to use . However, for ease of brushing or for application by spraying can be diluted with suitable amount of Duracoat White Spirit to adjust viscosity.

## Duracoat Single Pack Polywood Seal Varnish

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material. All traces of Wax or Oil should be removed by power sanding particularly if wax had been used on the surface before. Moisture Content of surface should not exceed 12% prior to coating.

#### New Wooden Surface:

Apply one coat of Basco NC Sanding sealer. Allow to dry for 2-3 hours. Sand the surface using emery paper, wipe off the dust and dirt, then apply 2-3 coats of Duracoat Single pack Polywoodseal Varnish.

#### Previously painted surface :

Remove all the previously coated surface by scraping or sanding. Then apply Duracoat Single pack Polywoodseal Varnish, as per the procedure for new wood surface.

### Health & Safety Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist seek medical advice
- Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment's.
- Fire Hazard: Flammable

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

### Note

- **Container should be closed tightly after use to avoid skin formation.**

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya  
Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)