



# Duracoat Aqua Wood Finish

## Features

- Highly durable finish
- Contains UV filters to prevent color fade
- Resists blistering and flaking
- Excellent adhesion to properly prepared wooden substrates
- Easy to apply, excellent flow and levelling

## General Description

The new generation 100% acrylic water based exterior durable coating for wooden window/door/door frames. The pure acrylic resin with its own unique qualities gives outstanding beauty and protection to windows, doors and other exterior woodwork.


## Recommended for

Ideally suitable for interior and exterior woodworks.

## Limitations

Do not apply when the temperature is below 10°C.

## Product Information

<b>Colour Range :</b> Available in a wide range of colors from Duracoat WoodTech Shade Card	<b>Technical Data</b>	
	<b>Finish</b>	Gloss, Satin and Matt
	<b>Spread Rate</b>	The spread rate will vary with porosity and type of substrate. For uncoated new work 6-8 Sq.Mt./Ltr for the first coat and 10-12 Sq.Mt./Ltr for subsequent coats
<b>Special Colors :</b> Special colors can be made available on request	<b>Drying time</b> - Surface dry - Recoating time	20-30 mins 4 hours
<b>Pack sizes :</b> 0.5 ltr, 1ltr, 4 ltrs	<b>Application</b>	By Brush, Rollers, Conventional Spray
<b>Technical Assistance:</b> If in doubt please contact our Technical department on 6823555/954	<b>Thinning</b>	This product is ready to use. Do not thin.
	<b>Cleaning</b>	Clean all equipments with water. Spray equipment should be given a final rinse with Duracoat White Spirit to prevent rusting
	<b>Volatile Organic Compounds (VOC)</b>	< 75 gm/l

---

## Duracoat Aqua Wood Finish

### Surface Preparation

All surfaces to be painted must be clean, dry and free from dusts, grease or any loose material.

**New Surfaces:** Sand the wooden substrate well, remove all dust. Apply one coat of Duracoat Aqua Wood Finish and let it dry. Lightly sand and clean the surface and apply two more generous coats.

**Previously Varnished Surfaces in poor conditions:** Remove all previous varnish back to bare wood, then sand well, remove all dust. Apply one coat of Duracoat Aqua Wood Finish and let it dry. Lightly sand and clean the surface and apply two more generous coats.

**Previously Varnished Surfaces:** If the previously varnished area is sound (no sign of flaking peeling cracking etc) then sand well, remove all dust. Apply one coat of Duracoat Aqua Wood Finish and let it dry. Lightly sand and clean the surface and apply two more generous coats.

### Precautions

- Ensure good ventilation during application and drying
- Store the product at ambient conditions in well ventilated locations and away from the source of ignition and fire
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persists seek medical advise
- Do not inhale or inject. In case of inhalation move to fresh air and seek medication attention if symptoms persists in both the cases.
- Use appropriate personal protective equipments.

### Application

- Stir thoroughly before and during use
- Always use good quality brush
- Try to paint in one motion
- Always pre test on a small area first

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to MSDS for additional health and safety information**

### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. representative to obtain the most recent Product Data Information

Basco Products (K) Ltd. P.O. Box 34424-00100, North Airport Road, Embakasi, Nairobi, Kenya  
Tel:+254-20-6823555/954, Fax: +254-20-6823956 [www.bascopaints.com](http://www.bascopaints.com)